













Features

- Price Integrity 
- Wireless Transmission 
- Eco-Friendly 
- Scalable System 
- Wide Operating Temperature 



-  Water Resistant, IP67
-  High Contrast Display
-  Durable Battery Life
-  Easy To Install
-  Price Automation

3 Simple Steps



TAP

1) Tap e.Label of the item, it will then trigger the signal transmission of PLU to the scale.



WEIGH






2) Place the item onto the scale platter and select the icon (PLU) belonging to the item.



PRINT

3) Select print label and paste onto the tray or item.

Specifications

Model	e.Label 1.54"	e.Label 2.7"	e.Label 4.2"
Image			
Dimension WxHxD (mm)	50 x 61 x 28	80 x 55 x 16	101 x 87 x 16
Screen Size	1.54"	2.7"	4.2"
Display Size (Pixels)	152 x 152	264 x 176	400 x 300
Display Size (mm)	28 x 28	58 x 39	86 x 65
Resolution (DPI)	140	117	120
Case Colour	White	Black	Black
Display Colours  	Black, White		
Operating Temperature	0°C to 40°C		
Operating Humidity	85% Max. RH Non-Condensing		
Frequency Band	2.410GHz ~ 2.480GHz		
NFC	Yes		
IP Rating	IP67		
Compliance	CE, RoHS, FCC, RCM		
Power Source	1 x DC Cell Button Battery 3.0V (Non-Serviceable)	3 x DC Cell Button Battery 3.0V (Non-Serviceable)	
Net Weight	55 g	70 g	120 g

*Subject to environmental condition and usage



• Specifications are subject to change without prior notice

DIGI SINGAPORE PTE. LTD.

4 Leng Kee Road #05-02/03/04/05/11/12
SIS Building SINGAPORE 159088
TEL : +65 6472 2996
SALES : +65 6378 5387
FAX : +65 6863 4614
URL : www.digisystem.com/sg/
E-MAIL : customer_support@sg.digi-group.com

TERAOKA SEIKO Co., Ltd.

13-12 Kugahara 5-chome, Ohta-ku,
Tokyo 146-8580, JAPAN
TEL : +81-3-3752-2131
FAX : +81-3-3752-5562
URL : www.digisystem.com